

LISTING OF THE CLAIMS:

1. (Withdrawn) A method for migrating from a source user authenticator having a source datastore containing encrypted password data and other unencrypted data, to a target user authenticator having a target datastore, the method comprising:

reading the unencrypted data from source datastore, wherein the source datastore contains encrypted password data and other unencrypted data, wherein the unencrypted data represents data for multiple users each having an identification and an associated password;

converting the unencrypted data to be compatible with target datastore;

populating the target datastore with the converted data;

implementing a servlet that:

intercepts an identification from a user seeking access to information protected by the target user authenticator,

locates the corresponding identification in the target datastore, and

determines that the target datastore does not include a password associated with the identification; and

implementing a password capture process that:

intercepts a password from the user associated with the received identification,

submits the received identification and received password to the source user authenticator,

monitors the source user authenticator for an approval response prior to populating the target datastore, and

populates the target datastore with the received password associating the received password with the corresponding identification, upon receipt of an approval response from the source user authenticator.

2. (Withdrawn) The method of claim 1 further comprising the action of:

if, after determining whether the target datastore includes a password associated with the identification, the target datastore does include a password associated with the identification, then authenticate the identification and password using the target user authenticator.

3. (Withdrawn) The method of claim 1, wherein the actions of receiving a password from a user further comprises:

receiving a password in a single submission from the user in conjunction with receiving the identification from the user.

4. (Withdrawn) The method of claim 1, wherein the action of receiving a password from a user further comprises:

receiving a password in a submission from the user after the initial submission of the identification from the user.

5. (Withdrawn) The method of claim 1, wherein the action of receiving a password from a user further comprises:

prompting for and receiving a password from the user after the initial submission of the identification from the user.

6. (Withdrawn) The method of claim 1, wherein the action of receiving a password from a user further comprises:

prompting for and receiving the identification and a password from the user after the initial submission of the identification from the user.

7. (Withdrawn) The method of claim 6, wherein the action of prompting for and receiving the identification and a password from the user after the initial submission of the identification from the user occurs after determining that the target datastore does not include a password associated with the identification; and,

wherein the action further comprises using the source user authenticator to prompt for and receive the identification and a password from the user after the initial submission of the identification from the user.

8. (Withdrawn) The method of claim 7, wherein while the source user authenticator is receiving the submitted password from the user, capturing the password provided by the user in response to the source authenticator prompting and using the captured password as the received password.

9. (Withdrawn) The method of claim 7, wherein after receipt of an approval response from the source user authenticator, capturing the password provided by the user in response to the source authenticator prompting and using the captured password as the received password.
10. (Withdrawn) The method of claim 1, wherein the target datastore is an LDAP compliant directory service.
11. (Withdrawn) The method of claim 1, wherein the target datastore is a relational database.
12. (Withdrawn) The method of claim 10, wherein the source datastore is a relational database.
13. (Withdrawn) The method of claim 11, wherein the source datastore is a relational database.
14. (Withdrawn) The method of claim 1, wherein the user is a person.
15. (Withdrawn) The method of claim 1, wherein the user is a software object.

16. (Currently Amended) A method for populating password data in a target datastore of a target user authenticator after migration from a source user authenticator having a source datastore, while also responding to user requests for information, the method comprising:

migrating the source ~~user~~ datastore ~~with the source user authenticator~~ to the target datastore ~~with the target user authenticator~~, wherein the ~~target user~~ source datastore comprises user identification data and user authentication data, wherein the source datastore is associated with a source user authenticator, wherein the target datastore is associated with a target user authenticator, and wherein the target user authenticator is in communication with the source user authenticator;

intercepting, by an interceptor, a request to the source user authenticator from a user seeking access to information protected by the target user authenticator, wherein the ~~the~~ interceptor prompts the user for an identification, receives the identification from the user, locates ~~the a~~ corresponding identification in the target datastore, and ~~determines whether the target datastore includes a password associated with the identification~~ searches the target datastore for a password associated with the identification; and

~~searching the target datastore for the password associated with the identification, wherein upon the determination~~ determining that there is no password in the target datastore associated with the identification:

forwarding ~~allowing~~ the original intercepted request ~~to go through~~ to the source user authenticator,

using the source user authenticator to prompt for and receive the identification and a password from the user,

capturing the password provided to the source user authenticator by the user in response to prompting by the source authenticator ~~prompting and using the captured password as the received password,~~

monitoring the source user authenticator for an approval response,

populating the target datastore with the ~~received~~ captured password upon receipt by the target datastore of an approval response from the source user authenticator, and associating the ~~received~~ captured password with the corresponding identification.

17. (Original) The method of claim 16, wherein after populating the target datastore, further comprising prompting for and receiving from the user the password associated with the identification.

18. (Original) The method of claim 17, wherein the action of prompting for and receiving from the user the password associated with the identification comprises prompting for and receiving from the user the identification and the password associated with the identification.

19. (Withdrawn) A method for checking for populated password data to a target datastore of a target user authenticator after migration from a source user authenticator having a source datastore, while also responding to user requests for information comprising:

with an interceptor:

intercepting a request to the source user authenticator from a user seeking access to information protected by the target user authenticator;

prompting the user for an identification;

receiving the identification from the user;

locating the corresponding identification in the target datastore and determining whether the target datastore includes a password associated with the identification; and

if the target datastore does include a password associated with the identification, then:

authenticating the identification and password using the target user authenticator.

20. (Withdrawn) The method of claim 19, wherein after determining that target datastore does include a password associated with the identification further comprising prompting for and receiving from the user the password associated with the identification.

21. (Withdrawn) The method of claim 20, wherein the action of prompting for and receiving from the user the password associated with the identification comprises prompting for and receiving from the user the identification and the password associated with the identification.

22. (Currently Amended) A method for populating password data to a target datastore of a target user authenticator after migration from a source user authenticator having a source datastore, while also responding to user requests for information, the method comprising:

migrating the source user datastore ~~with the source user authenticator~~ to the target datastore ~~with the target user authenticator~~, wherein the ~~target user~~ source datastore comprises user identification data and user authentication data, wherein the source datastore is associated with a source user authenticator, wherein the target datastore is associated with a target user authenticator, and wherein the target user authenticator is in communication with the source user authenticator;

intercepting, with an interceptor, a request to the source user authenticator from a user seeking access to information protected by the target user authenticator, wherein the interceptor prompts the user for an identification, receives the identification from the user, locates ~~the a~~ a corresponding identification in the target datastore, and ~~determines whether the target datastore includes a password associated with the identification~~ searches the target datastore for a password associated with the identification;

forwarding allowing the original intercepted request ~~to go through~~ to the source user authenticator ~~to the target user authenticator~~ upon determining that the target datastore does not include a password associated with the identification;[[,]]

using the source user authenticator to prompt for and receive the identification and a password from the user, the target user authenticator: monitors the source user authenticator for an approval response, and upon an approval response from the source user authenticator, captures the password provided to the source user authenticator by the user in response to prompting by the source authenticator ~~prompting and using the captured password as the received password~~, populates the target datastore with the ~~received~~ captured password, and associates the ~~received~~ captured password with the corresponding identification.

23. (Original) The method of claim 22, wherein after populating the target datastore, further comprising prompting for and receiving from the user the password associated with the identification.

24. (Original) The method of claim 23, wherein the action of prompting for and receiving from the user the password associated with the identification comprises prompting for and receiving from the user the identification and the password associated with the identification.